## SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : GLASSBOND P641/M PASTE

REACH notes : Mixture- Substances contained in this product that are

not classified as hazardous have been/will be registered for

REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : Lamp capping adhesive

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd

West Side Industrial Estate

Jackson Street St. Helens

Merseyside WA9 3AT United Kingdom

Telephone +44(0)1744 730334 Fax +44(0)1744 451661

Email technical@glassbond.co.uk

**1.4 Emergency telephone** +44(0)1744 730334

**number** (GMT, English spoken, Mon-Friday; 08.30-16.30)

#### **SECTION 2: HAZARDS IDENTIFICATION \***

## 2.1 Classification of the mixture: calculation method

**2.1.1** Regulation (EC) No. 1272/2008(CLP)

Physical/Chemical NOT CLASSIFIED Human health NOT CLASSIFIED Environmental NOT CLASSIFIED

**2.1.2** Directive 1999/45/EC(DPD) Not available

2.2 Label elements According to Regulation (EC) No. 1272/2008(CLP)

Hazard pictogram(s)

Print date 28/09/2017

GHS NO PICTOGRAM REQUIRED

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

SIGNAL WORD (S) NOT CLASSIFIED

HAZARD

STATEMENT(S)

PRECAUTIONARY STATEMENT(S)

2.3 Other Hazards

PBT: This mixture contains no substances considered as PBT vPvB: This mixture contains no substances considered as vPvB

2.4 Additional information

For full text of H/P phrases see section 16 if not written out in full

above.

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*

**3.1** Substances . (This product is a mixture according to EU legislation.)

**3.2** Mixture of Synthetic resin dissolved in industrial denatured spirits, containing inert fillers.

Hazardous ingredient	% w/w	CAS N°	EC N°	REACH N°	CPL EC 1272/2008
Hexamine	<1	100-97-0	202-905-8	Not available	H228: Flammable solid. H317: May cause an allergic skin reaction.
Industrial denatured spirit	6-8	64-17-5	200-578-6	Ethanol mixture contains 5% mehanol	H225 Highly flammable Liquid and Vapour H371 May cause damage to organs if swallowed in contact with skin and via inhalation

#### 3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

General advice Immediately remove contaminated clothing, take care not to contaminate

unaffected areas.

Inhalation Contains component irritating by inhalation. Move the exposed person to fresh

air. Seek medical attention.

Eyes Rinse immediately with running water for at least 15 minutes holding the

eyelid open; consult an eye specialist.

Skin Wash thoroughly with water and soap

If skin irritation or rash occurs get medical attention (P333+P313)

Ingestion Immediately rinse the mouth with water and drink plenty of water. Obtain

medical attention immediately, show this safety data sheet.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms Eye contact- May cause temporary eye irritation.

Risks No information available

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

#### **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 Extinguishing media:

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and extinguish flames.

Unsuitable: High pressure water jet

#### 5.2 Special hazards arising from the mixture

Harmful vapours. Thermal decomposition or burning may release toxic oxides of nitrogen and other toxic gases.

#### 5.3 Advice for fire fighters

Use full protective clothing and self-contained breathing apparatus.

**Further information**: The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1 Personal Precautions, protective equipment and emergency procedures

Use personal protective clothing. Eliminate sources of ignition

#### **6.2 Environmental Precautions**

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

#### 6.3 Methods and material for containment and cleaning up

Collect spillage by sweeping or scraping up. keep in suitable closed container for disposal.

#### **6.4** Reference to other sections

For personal protection see section 8 and disposal section 13

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling

PPE see section 8. Contaminated clothing should not be allowed out of the workplace (P272). Wash contaminated

clothing before reuse (P363)

Advice on protection Sources of ignition should be kept well clear. Take against fire and explosion precautionary measures against static discharges if delivered

in plastic packaging.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. The paste should be stored under cover, in a well ventilated, cool, dry place and away from direct sunlight, heat or sources of ignition.

Protect from temperatures below : minus 5 °C  $\,$ 

Protect from temperatures above  $: 35 \, ^{\circ}\text{C}$ 

Suitable storage materials : Original containers.

Higher temperatures and humidity will reduce the shelf life of the product. Under

normal conditions (21°C) a shelf life of 8 weeks or more is possible.

7.3 Specific end use(s) As per section 1.2

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 Control parameters

## 8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

Industrial methylated	TWA	mg/m³ 1920	ppm 1000	Note (EH40 UK) OES 8 hr
spirits (IMS)	STEL			(EH40 UK)
	TWA STEL			(EH40 UK) (EH40 UK)
	TWA STEL			(EH40 UK) (EH40 UK)

8.1.2 Biological limit value Not available8.1.3 PNECs and DNELs Not available

#### 8.2 Exposure Controls

**8.2.1** Appropriate engineering controls: Effective exhaust ventilation system

#### **8.2.2** Personal Protective Equipment:

Eye/face Tightly fitting safety goggles (e.g. EN166) Protection

Skin Protection/ Gloves: Chemical resistant gloves (e.g. EN374) Butyl rubber: 0.7 mm coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with

coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE manufacturer. Replace immediately if signs of degradation are

Other observed. Wear closed work clothing.

Respiratory Chemical cartridge if there is a risk of breathing vapours

Protection Cartridge: e.g. EN14387 Type A (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

#### 8.2.3 Environmental exposure controls

No special environmental precautions required

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1 information on basic physical and chemical properties

Appearance Odour	Thick Paste alcoholic	COLOUR ODOUR THRESHOLD ppm	Green Not Available
pH Value Melting Point/Freezing pt INITIAL BOILING POINT/RANGE FLASHPOINT °C	Not available Not applicable 78°C (IMS) Not applicable	RELATIVE DENSITY SOLUBILITY IN WATER PARTITION COEFFICIENT (n-octanol/water)	1.9 g/ml <1 % soluble 0.32 (IMS)
EVAPORATION RATE FLAMMABILITY (SOLID/GAS) UPPER EXPLOSIVE LIMIT LOWER EXPLOSIVE LIMIT VAPOUR PRESSURE VAPOUR DENSITY (AIR=1)	Not applicable Not applicable Not Available >1.3 % (IMS) Not applicable 1.6 (IMS)	AUTO IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE °C VISCOSITY mPa.s @ 25°C EXPLOSIVE PROPERTIES OXIDIZING PROPERTIES	Not available Not available Not applicable Not available Not oxidising

#### 9.2 Other information

Partially soluble in alcohols

#### **SECTION 10: STABILITY AND REACTIVITY**

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical Stability	Stable under recommended storage and handling conditions.
10.3	Possibility of	No dangerous reaction known under conditions of normal use
	Hazardous reactions	
10.4	Conditions to Avoid	No decomposition if stored and applied as directed.
10.5	Incompatible	Acids, strong oxidising agents
	materials	
10.6	Hazardous	No hazardous decomposition products if stored and handled
	Decomposition	as prescribed/ indicated.
	Products.	Fire creates oxides of carbon and nitrogen, formaldehyde.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1 Information on toxicological effects of the mixture

Acute toxicity			at are hazardous by the following on and ingestion.
LD 50 ORAL TOXICITY RATS	9200	mg/kg	Hexamine
LD <sub>50</sub> DERMAL TOXICITY RATS	2000	mg/kg	Hexamine
LC 50 INHL TOXICITY IN RATS		mg/kg	
LD 50 ORAL TOXICITY RATS	6200-17800	mg/kg	Industrial methylated spirits
LD <sub>50</sub> DERMAL TOXICITY RABBITS	>20000	mg/kg	Industrial methylated spirits
LC 50 INHL TOXICITY IN RATS	>20000	mg/lt/4hr	Industrial methylated spirits

Skin corrosion/ irritation	May cause irritation
Serious eye damage / irritation	May cause irritation

**Respiratory or skin sensitisation** The product contains Hexamine which are skin

sensitising. Not classified Not classified

Germ cell mutagenicity Carcinogenicity

Date Revised : 28.09.2017 Revision: 5

Product : GLASSBOND P641/M PASTE

Reproductive toxicity Not classified **STOT SE (SINGLE exposure)** Not classified **STOT RE (REPEATED exposure)** Not classified **Aspiration hazard** Not classified

#### 11.2 Other information

Skin sensitisation might occur in people with hypersensitive skin.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 **Toxicity**

LL <sub>50</sub> Fish EC <sub>50</sub> Invertibrates EL <sub>50</sub> Algae	(96 hr) (48 hr) (72hr)	41000 (hexamine) 36000 (hexamine)	mg/l	Lepomis macrochirus Daphnia magna Selenastrum capricornutum
LL <sub>50</sub> Fish EC <sub>50</sub> Invertibrates EL <sub>50</sub> Algae	(96 hr) (48 hr) (72hr)		mg/l	Lepomis macrochirus Daphnia magna Selenastrum capricornutum

Micro organisms/ effect upon activated sludge

EC<sub>50</sub> Bacteria (3.0 hr)mg/l Activated sludge, domestic

#### 12.2 **Persistance and** Organic resin components are not readily biodegradable.

degradability Solvent is readily biodegradable

#### 12.3 **Bioaccumulative potential** Not available

#### 12.4 Mobility in soil Sinks in water. A small percentage (<10%) is water

soluble. If the product enters soil, it will be mobile and

may contaminate groundwater.

#### 12.5 Results of PBT and vPvB

assessment

PBT: This mixture contains no substances considered

as PBT

vPvB: This mixture contains no substances considered

as vPvB

#### 12.6 Other adverse effects

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

#### **SECTION 13: DISPOSAL CONSIDERATION**

#### 13.1 Waste treatment methods

The preparation must be disposed of by special means. Dispose by incineration or landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

#### 13.2 Additional information

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

Dispose of contents/ container according to the end user disposal procedure (P501)

#### **SECTION 14 - TRANSPORT INFORMATION**

**14.1 UN number** NOT CLASSIFIED

ADR

RID

**IMDG** 

**IATA** 

ADN

**14.2 Proper shipping name** NOT CLASSIFIED

ADR

RID

IMDG

IATA ADN

14.3 Transport Hazard Class NOT CLASSIFIED

ADR

**RID** 

**IMDG** 

**IATA** 

ADN

14.4 Packing Group NOT CLASSIFIED

**ADR** 

RID

**IMDG** 

**IATA** 

ADN

14.5 Environmental hazards NOT CLASSIFIED

ADR

RID

**IMDG** 

IATA

ADN

#### 14.6 Special Precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage

Date Revised : 28.09.2017 Revision : 5

Product : GLASSBOND P641/M PASTE

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

#### **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the mixture

**EU** Legislation

Commission Regulation (EC) No 474/2014 of  $8^{th}$  May 2014 amending Annex XVII to Regulation (EC) No 1907/2006

Commission Regulation (EC) No 944/2013 of 2<sup>nd</sup> October 2013 (5<sup>th</sup> ATP) amending Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Waste Framework Directive 2008/98/EC

Employment restrictions: Observe employment restrictions for young people, for child bearing mothers/ nursing and for women of child-bearing age.

#### 15.2 Chemical Safety Assessment

Exposure scenarios are not required for this mixture because it is not classified as dangerous according to Directive 67/548/EEC and assessed to be not PBT/vPvB. No risk management measures as defined by REACH have been identified.

#### **SECTION 16: OTHER INFORMATION \***

\* SECTIONS REVISED 2,3,16 Supercedes date 09.09.2014 The Safety Data Sheets have been revised throughout in accordance with CLP/GHS requirements

Legend

PBT Persistent, Bioaccumulative and Toxic VPVB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

H228 Flammable solid.

H317 May cause an allergic skin reaction. H225 Highly flammable Liquid and Vapour

H371 May cause damage to organs if swallowed in contact with skin and via

inhalation

Training advice General industrial hygiene practice.

Manual handling

Further information

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to it's accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.