

Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010  
 Date Revised : 31.10.2018 Revision : 08  
 Product : **ELECTRICAL CEMENT POWDER N°315**

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product Identifier

Product name : **ELECTRICAL CEMENT POWDER N°315**  
 REACH notes : Mixture- Substances contained in this product that are not classified as hazardous have been/will be registered for REACH at the appropriate time.

### 1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : High temperature adhesive and sealant  
 Uses advised against : No other uses

### 1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd  
 West Side Industrial Estate  
 Jackson Street  
 St. Helens  
 Merseyside WA9 3AT  
 United Kingdom

Telephone +44(0)1744 730334  
 Fax +44(0)1744 451661  
 Email technical@glassbond.co.uk

1.4 **Emergency telephone number** +44(0)1744 730334  
 (GMT, English spoken, Mon-Friday; 08.30-16.30)

## SECTION 2 : HAZARDS IDENTIFICATION\*

### 2.1 Classification of the mixture: calculation method

2.1.1 Regulation (EC) No. 1272/2008(CLP)  
 Physical/Chemical NOT CLASSIFIED  
 Human health STOT RE 2 (inhalation)  
 Environmental NOT CLASSIFIED

2.1.2 Directive 1999/45/EC(DPD) Not available

2.2 **Label elements According to Regulation (EC) No. 1272/2008(CLP)**  
 STOT RE 2



GHS08

SIGNAL WORD (S) WARNING

HAZARD STATEMENT(S) H373 May cause damage to lungs through prolonged or repeated exposure via inhalation

PRECAUTIONARY STATEMENT(S) P260 Do not breathe dust  
P314 Get medical attention if unwell

### 2.3 Other Hazards

PBT : This mixture contains no substances considered as PBT  
vPvB: This mixture contains no substances considered as vPvB

**2.4 Additional information** For full text of H/P phrases see section 16 if not written out in full above.

---

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS\*

**3.1** Substances . (This product is a mixture according to EU legislation.)

**3.2** Mixture of inorganic powders

<b>Hazardous ingredient</b>	<b>% w/w</b>	<b>CAS N°</b>	<b>EC N°</b>	<b>REACH N°</b>	<b>CPL EC 1272/2008</b>
Silica powder	35-45	14808-60-7	238-878-4	Exempted Annex v 7	H373: STOT RE 2

### 3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

## **SECTION 4: FIRST AID MEASURES**

### **4.1 Description of first aid measures**

General advice	Take off contaminated clothing and wash before re-use (P362), take care not to contaminate unaffected areas.
Inhalation	IF INHALED remove victim to fresh air and keep at rest in a position comfortable for breathing. (P304+P340)
Eyes	IF IN EYES rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.( P305 + P351 + P338) If eye irritation persists: Get medical attention (P337+P313)
Skin	IF ON SKIN wash exposed areas thoroughly after handling (P264) If skin irritation or rash occurs get medical attention (P332+P313)
Ingestion	IF SWALLOWED: Rinse mouth (P301+P330). Obtain medical attention immediately, show this safety data sheet.

### **4.2 Most important symptoms and effects, both acute and delayed**

Symptoms	Eye contact- May cause irritation
Risks	No information available

### **4.3 Indication of any immediate medical attention and special treatment needed**

Treatment	Treat according to symptoms (decontamination, vital functions), no known specific antidote.
-----------	---

---

## **SECTION 5 : FIRE FIGHTING MEASURES**

### **5.1 Extinguishing media:**

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and extinguish flames for surrounding materials.

Unsuitable: High pressure water jet.

### **5.2 Special hazards arising from the mixture**

The powder will not burn but the packaging is combustible.

### **5.3 Advice for fire fighters**

Use full protective clothing and self-contained breathing apparatus.

**Further information:** The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

---

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal Precautions, protective equipment and emergency procedures**

Use personal protective clothing.

### **6.2 Environmental Precautions**

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

### **6.3 Methods and material for containment and cleaning up**

Collect spillage by sweeping or industrial vacuum cleaner. keep in suitable closed container for disposal

### **6.4 Reference to other sections**

For personal protection see section 8 and disposal section 13

---

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling Avoid the formation and deposition of dust. Use only outdoors or in a well ventilated area (P271). For PPE see section 8. Wash contaminated clothing before reuse (P363)

Advice on protection against fire and explosion Normal measures for preventive fire protection  
 Take precautionary measures against static discharge if using plastic packaging.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Store locked up (P450), under cover, in a well ventilated, cool, dry place and away from direct sunlight or heat.  
 Protect from temperatures below : Not applicable  
 Protect from temperatures above : 40 °C  
 Suitable storage materials : Original containers.  
 Higher temperatures and humidity will reduce the shelf life of the product and may cause the powder to form lumps. The powder will also be difficult to mix into a paste. Under normal conditions (21°C) a shelf life of 12 months or more is possible.

### 7.3 Specific end use(s) As per section 1.2

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### 8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

		mg/m <sup>3</sup>	ppm	Note
Silica crystalline	TWA	-	inhalable	(EH40 UK) OES 8 hr
	TWA	0.3	respirable	(EH40 UK)
Silica crystalline	TLV-TWA	0.1	respirable	(ACIGH)
	STEL	-		
	TWA	-		
	TWA	-		
	STEL	-		

**8.1.2 Biological limit value** Not available

**8.1.3 PNECs and DNELs** Not available

### 8.2 Exposure Controls

**8.2.1 Appropriate engineering controls:** Effective exhaust ventilation system

#### 8.2.2 Personal Protective Equipment:

Eye/face Protection Tightly fitting safety goggles (e.g. EN166)

Skin Protection/ Hand Gloves: Chemical resistant gloves (e.g. EN374) Butyl rubber: 0.7 mm coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE manufacturer. Replace immediately if signs of degradation are observed.

Other Wear closed work clothing.

Respiratory Protection In the case of insufficient ventilation or severe dusts  
 Cartridge: e.g. EN143 Type P-S (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

#### 8.2.3 Environmental exposure controls

Local exhaust ventilation and take precautionary measures against static discharge.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 information on basic physical and chemical properties

APPEARANCE	Fine powder	COLOUR	Cream
ODOUR	None	ODOUR THRESHOLD ppm	Not Available
pH VALUE	5-8	RELATIVE DENSITY	2.7 g/ml
MELTING POINT/FREEZING PT	Not applicable	SOLUBILITY IN WATER @ 20°C	~23 g/100g
INITIAL BOILING POINT/RANGE	Not applicable	PARTITION COEFFICIENT	Not available
FLASHPOINT °C	Not applicable	(n-octanol/water)	
EVAPORATION RATE	Not applicable	AUTO IGNITION TEMPERATURE	Not available
FLAMMABILITY (SOLID/GAS)	Not applicable	DECOMPOSITION TEMPERATURE °C	Not available
UPPER EXPLOSIVE LIMIT	Not Available	VISCOSITY mPa.s @ 25°C	Not applicable
LOWER EXPLOSIVE LIMIT	Not Available	EXPLOSIVE PROPERTIES	Not available
VAPOUR PRESSURE	Not applicable	OXIDIZING PROPERTIES	Not oxidising
VAPOUR DENSITY (AIR=1)	Not applicable		

### 9.2 Other information

## SECTION 10 : STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	Stable under normal conditions.
<b>10.2 Chemical Stability</b>	Stable under recommended storage and handling conditions.
<b>10.3 Possibility of Hazardous reactions</b>	No dangerous reaction known under conditions of normal use
<b>10.4 Conditions to Avoid</b>	No decomposition if stored and applied as directed.
<b>10.5 Incompatible materials</b>	Incompatible with alkaline materials, iron containing materials.
<b>10.6 Hazardous Decomposition Products.</b>	No hazardous decomposition products if stored and handled as prescribed/ indicated.

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects of the mixture

<b>Acute toxicity</b>	Contains components that are hazardous by the following routes : inhalation.	
LD <sub>50</sub> ORAL TOXICITY IN RATS	-	mg/kg
LD <sub>50</sub> DERMAL TOXICITY RABBITS	-	mg/kg
LC <sub>50</sub> INHL TOXICITY IN RATS	-	g/m <sup>3</sup>
LD <sub>50</sub> DERMAL TOXICITY RABBITS	-	mg/kg
LC <sub>50</sub> ORAL TOXICITY IN RATS	-	mg/kg
LD <sub>50</sub> DERMAL TOXICITY RATS	-	mg/kg
<b>Skin corrosion/ irritation</b>	Irritating	
<b>Serious eye damage / irritation</b>	Irritating	
<b>Respiratory or skin sensitisation</b>	Not classified	
<b>Germ cell mutagenicity</b>	Not classified	
<b>Carcinogenicity</b>	Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis cause by deposition in the lungs of fine respirable particles of crystalline silica.	

<b>Reproductive toxicity</b>	Not classified
<b>Specific Target Organ Toxicity (Repeated Exposure)</b>	STOT RE2
<b>Specific Target Organ Toxicity (Single Exposure)</b>	Not classified
<b>Aspiration hazard</b>	Not classified

**11.2 Other information**

In 1997, IARC (International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans.

**SECTION 12 : ECOLOGICAL INFORMATION****12.1 Toxicity**

LL <sub>50</sub> Fish	(96 hr)	Not available	mg/l	Brachydanio rerio
EC <sub>50</sub> Invertebrates	(48 hr)		mg/l	Daphnia magna
EL <sub>50</sub> Algae	(72hr)		mg/l	Selenastrum capricornutum
LL <sub>50</sub> Fish	(96 hr)		mg/l	Lepomis macrochirus
EC <sub>50</sub> Invertebrates	(48 hr)		mg/l	Daphnia magna
EL <sub>50</sub> Algae	(72hr)		mg/l	Selenastrum capricornutum

Micro organisms/ effect upon activated sludge

EC <sub>50</sub> Bacteria	(3.0 hr)	mg/l	Activated sludge, domestic
---------------------------	----------	------	----------------------------

**12.2 Persistence and degradability** Not biodegradeable

**12.3 Bioaccumulative potential** Not available

**12.4 Mobility in soil** Sinks in water. A proportion (~23%) is water soluble. If the product enters soil, it will be mobile and may contaminate groundwater.

**12.5 Results of PBT and vPvB assessment** PBT : This mixture contains no substances considered as PBT

vPvB: This mixture contains no substances considered as vPvB

**12.6 Other adverse effects**

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

---

**SECTION 13 : DISPOSAL CONSIDERATION****13.1 Waste treatment methods**

Dispose of contents/ container according to the end user disposal procedure (P501).  
Dispose by landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

**13.2 Additional information**

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

---

**SECTION 14 - TRANSPORT INFORMATION**

**14.1 UN number** NOT CLASSIFIED

ADR  
RID  
IMDG  
IATA  
ADN

**14.2 Proper shipping name** NOT CLASSIFIED

ADR  
RID  
IMDG  
IATA  
ADN

**14.3 Transport Hazard Class** NOT CLASSIFIED

ADR  
RID  
IMDG  
IATA  
ADN

**14.4 Packing Group** NOT CLASSIFIED

ADR  
RID  
IMDG  
IATA  
ADN

**14.5 Environmental hazards** NOT CLASSIFIED

ADR  
RID  
IMDG  
IATA  
ADN

**14.6 Special Precautions for user**

Not classified as dangerous in the meaning of transport regulations

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code**

Not applicable

---

Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 31.10.2018

Revision : 08

Product : **ELECTRICAL CEMENT POWDER N°315**

---

**SECTION 15 : REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the mixture**

EU Legislation

Commission Regulation (EC) No 474/2014 of 8<sup>th</sup> May 2014 amending Annex XVII to Regulation (EC) No 1907/2006Commission Regulation (EC) No 944/2013 of 2<sup>nd</sup> October 2013 (5<sup>th</sup> ATP) amending Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Waste Framework Directive 2008/98/EC

Employment restrictions: Observe employment restrictions for young people, for child bearing mothers/ nursing and for women of child-bearing age.

**15.2 Chemical Safety Assessment**

Assessed to be not PBT/vPvB.

---

**SECTION 16 : OTHER INFORMATION\***

\* SECTIONS REVISED 7, 10 Supercedes date 17.08.2017  
The Safety Data Sheets have been revised throughout in accordance with CLP/GHS requirements

Legend

PBT Persistent, Bioaccumulative and Toxic  
vPvB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

H373 May cause damage to lungs through prolonged or repeated exposure via inhalation

Training advice General industrial hygiene practice. Do not eat, drink or smoke when using this product (P270)

Further information

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.