# SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : Glassbond LED Capping Adhesive L546

REACH notes : Substances contained in this product that are not

classified as hazardous have been/will be registered for

REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : PC1, Adhesives, sealants

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION GLASSBOND (NW) LTD

WEST SIDE INDUSTRIAL ESTATE

JACKSON STREET St. Helens

MERSEYSIDE WA9 3AT UNITED KINGDOM

TELEPHONE +44(0)1744 730334 FAX +44(0)1744 451661

EMAIL TECHNICAL@GLASSBOND.CO.UK

1.4 EMERGENCY TELEPHONE +44(0)1744 730334

NUMBER (GMT, ENGLISH SPOKEN, MON-FRIDAY; 08.30-16.30)

#### SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the mixture:

Regulation (EC) No. 1272/2008(CLP)

STOT SE 3: H335; Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH202

Most important adverse effects:

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

## 2.2 Label elements (According to Regulation (EC) No. 1272/2008(CLP))



GHS0/

SIGNAL WORD (S) Warning

\_

HAZARD H315: Causes skin irritation
STATEMENT(S) H319: Causes serious eye irritation

STATEMENT(S) H319: Causes serious eye irritation H335: May cause respiratory irritation

EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds.

Keep out of the reach of children.

PRECAUTIONARY STATEMENTS:

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P337+313: If eye irritation persists: Get medical advice/attention.

P271: Use only outdoors or in a well-ventilated area.

P264: Wash thoroughly after handling.

P302+352: IF ON SKIN: Wash with plenty of water.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray. P304+340: IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P321: Specific treatment (see instructions on this label).

P362: Take off contaminated clothing.

P332+313: If skin irritation occurs: Get medical advice/attention. P403+233: Store in a well-ventilated place. Keep container tightly

closed.

P501: Dispose of contents/container to Registered Disposal Company in conjunction with local and national regulations.

## 2.3 Other Hazards

This product is not identified as a PBT/vPvB substance

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 HAZARDOUS INGREDIENTS: ETHYL-2-CYANOACRYLATE

EINECS	CAS	PBT/WEL	CLP Classification	Percent
230-391-5	7085- 85-0		Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315	85-99%

#### SECTION 4: FIRST AID MEASURES

## 4.1 Description of first aid measures

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

Inhalation Remove casualty from exposure ensuring one's own safety whilst doing so.

Consult a doctor.

Eyes Bathe the eye with running water for 15 minutes. Consult a doctor.

Skin Remove all contaminated clothes and footwear immediately unless stuck to

skin. Wash immediately with plenty of soap and water.

Ingestion Wash out mouth with water. Consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

Eyes There may be irritation and redness. The eyes may water profusely.

Skin There may be irritation and redness at the site of contact.

Ingestion There may be soreness and redness of the mouth and throat.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate/special treatment 

Eye bathing equipment should be available on the premises.

## SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media Suitable extinguishing media for the surrounding fire should be

used. Use water spray to cool containers.

5.2 Special hazards arising In combustion emits toxic fumes.

from the mixture

5.3 Advice for fire fighters Wear self-contained breathing apparatus. Wear protective clothing

to prevent contact with skin and eyes.

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, protective equipment and emergency procedures
Refer to section 8 of SDS for personal protection details. If outside do not approach from
downwind. If outside keep bystanders upwind and away from danger point. Mark out the
contaminated area with signs and prevent access to unauthorised personnel. Turn leaking
containers leak-side up to prevent the escape of liquid.

#### 6.2 Environmental Precautions

Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3 Methods and material for containment and cleaning up
Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

6.4 Reference to other sections Refer to section 8 of SDS.

#### SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling requirements Avoid direct contact with the substance. Ensure there is

sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions Store in a cool, well ventilated area. Keep container tightly

closed.

7.3 Specific end use(s) No data available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

WORKPLACE EXPOSUR	E LIMITS	RESPIRABLE DUST		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	1.5mg/m <sup>3</sup>	-	-

DNEL/PNE NO DATA AVAILABLE

#### 8.2 EXPOSURE CONTROLS

ENGINEERING MEASURES: ENSURE THERE IS SUFFICIENT VENTILATION OF THE AREA.

RESPIRATORY PROTECTION: SELF-CONTAINED BREATHING APPARATUS MUST BE AVAILABLE IN CASE OF EMERGENCY.

HAND PROTECTION: PROTECTIVE GLOVES.

EYE PROTECTION: TIGHTLY FITTING SAFETY GOGGLES. ENSURE EYE BATH IS TO HAND.

SKIN PROTECTION: PROTECTIVE CLOTHING.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Date Revised Revision: 01 : 12.08.2019

Product : GLASSBOND LED CAPPING ADHESIVE L546

#### 9.1 Information on basic physical and chemical properties

State Liquid Colour Colourless Irritating odour Odour Evaporation rate No data available Oxidising No data available

Solubility in water Insoluble Also soluble in Acetone Viscosity Non-viscous

Boiling point/range (°C) 150

Melting point/range (°C) No data available Flammability limits %: lower: No data available Flammability limits %: upper: No data available

Flash point (°C) 87 Autoflammability (°C) 500 Relative density  $1.05g/cm^{3}$ 

VOC (g/I) 20

Part.coeff. n-octanol/water No data available Vapour pressure No data available No data available рΗ

#### 9.2 No data available Other information

## SECTION 10: STABILITY AND REACTIVITY

10.1 10.2 10.3	Reactivity Chemical Stability Possibility of Hazardous reactions	Stable under recommended transport or storage conditions. Stable under normal conditions. Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on
10.4 10.5	Conditions to Avoid Incompatible materials	exposure to conditions or materials listed below. Heat. Strong oxidising agents.
10.6	Hazardous Decomposition Products	In combustion emits toxic fumes.

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

#### SECTION 11: TOXICOLOGICAL INFORMATION

Toxicity Value:	S			
Route	Species	Test	Value	Units
Dermal	RBT	LD50	2000	mg/kg

Oral RAT LD50 5000 mg/kg

Hazardous

Ingredients
Route Species Test Value

Route Species Test Value Units ORAL RAT LD50 >5 ml/kg

Relevant hazards for substance

Hazard Route Basis

Skin corrosion/irritation DRM Hazardous: calculated Serious eye damage/irritation OPT Hazardous: calculated STOT-single exposure INH Hazardous: calculated

### SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity
Ecotoxicity values
No data available

12.2 Persistence and degradability Biodegradable

12.3 Bioaccumulative potential No bioaccumulation potential

12.4 Mobility in soil Readily absorbed into soil

12.5 Results of PBT and vPvB assessment This product is not identified as

a PBT/vPvB substance

12.6 Other adverse effects Negligible ecotoxicity

#### SECTION 13: DISPOSAL CONSIDERATION

## 13.1 Waste treatment methods

Disposal operations Transfer to a suitable container and arrange for

collections by specialised disposal company

NB. The user's attention is drawn to the possible existence

of regional or national regulations regarding disposal

#### **SECTION 14: TRANSPORT INFORMATION**

Transport class This product does not require a classification for transport

Date Revised : 12.08.2019 Revision : 01

Product : Glassbond LED Capping Adhesive L546

#### **SECTION 15: REGULATORY INFORMATION**

15.1 Safety, health and environmental regulations/legislation specific for the substance or

mixture

Specific regulations Not applicable

#### **SECTION 16: OTHER INFORMATION**

Other information This safety data sheet is prepared in accordance with Commission

Regulation (EU) No 453/2010

Phrases used in EUH202: Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out

s.2 and s.3 of the reach of children.

H315: Causes skin irritation

H319: Causes serious eye irritation H335: May cause respiratory irritation

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.