# SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : GLASSBOND SAUEREISEN ELETROCEMENT POWDER N° X52
REACH notes : Mixture- Substances contained in this product that are

not classified as hazardous have been/will be registered for

UK/EU REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : Potting and encapsulation for electrical insulation

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd

West Side Industrial Estate

Jackson Street St. Helens

Merseyside WA9 3AT United Kingdom

Telephone +44(0)1744 730334 Fax +44(0)1744 451661 Email technical@glassbond.co.uk

**1.4** Emergency telephone +44(0)1744730334

**number** (GMT, English spoken, Mon-Friday; 08.30-16.30)

#### **SECTION 2: HAZARDS IDENTIFICATION\***

#### 2.1 Classification of the mixture: calculation method

**2.1.1** Regulation (EC) No. 1272/2008(CLP)

Physical/Chemical NOT CLASSIFIED Human health NOT CLASSIFIED Environmental NOT CLASSIFIED

**2.1.2** Directive 1999/45/EC(DPD) Not classified

# 2.2 Label elements According to Regulation (EC) No. 1272/2008(CLP)

NONE

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

SIGNAL WORD (S) NONE

HAZARD NONE

STATEMENT(S)

PRECAUTIONARY STATEMENT(S)

## 2.3 Other Hazards

PBT: This mixture contains no substances considered as PBT

vPvB: This mixture contains no substances considered as vPvB

**2.4 Additional** For full text of H/P phrases see section 16 if not written out in full above. **information** 

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS\*

- **3.1** Substances . (This product is a mixture according to EU legislation.)
- **3.2** Mixture of inorganic powders

Hazardous ingredient	% w/w	CAS Nº	EC N°	REACH Nº	CPL EC 1272/2008
Inhibitor	<1.5				Rep 2:H361d

# 3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

2/8

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

## **SECTION 4: FIRST AID MEASURES**

# 4.1 Description of first aid measures

General advice Immediately remove contaminated clothing, take care not to contaminate

unaffected areas.

Inhalation No emergency care anticipated, other than removal from exposure.

Eyes Rinse immediately with running water for at least 15 minutes holding the eyelid

open; consult an eye specialist.

Skin Wash thoroughly with water and soap

If skin irritation or rash occurs get medical attention (P333+P313)

Ingestion Immediately rinse the mouth with water and drink plenty of water. Obtain

medical attention immediately, show this safety data sheet.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms Eye contact- May cause temporary eye irritation.

Risks No information available

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

## **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 Extinguishing media:

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and extinguish flames for surrounding materials.

Unsuitable: High pressure water jet.

## 5.2 Special hazards arising from the mixture

The powder will not burn but the packaging is combustible.

#### **5.3** Advice for fire fighters

Use full protective clothing and self-contained breathing apparatus.

**Further information**: The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1 Personal Precautions, protective equipment and emergency procedures

Use personal protective clothing.

# 6.2 Environmental Precautions

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

# 6.3 Methods and material for containment and cleaning up

Collect spillage by sweeping or industrial vacuum cleaner. keep in suitable closed container for disposal

# 6.4 Reference to other sections

For personal protection see section 8 and disposal section 13

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

#### **SECTION 7: HANDLING AND STORAGE**

# 7.1 Precautions for safe handling

Advice on safe handling Avoid the formation and deposition of dust. Ensure thorough

ventilation of stores and work areas. For PPE see section 8 Contaminated clothing should not be allowed out of the workplace (P272). Wash contaminated clothing before reuse

(P363)

Advice on protection Normal measures for preventive fire protection

against fire and explosion Take precautionary measures against static discharge

if using plastic packaging.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. The powder should be stored under cover, in a well

ventilated, cool, dry place and away from direct sunlight or heat.

Protect from temperatures below: Not applicable

Protect from temperatures above  $: 40 \, ^{\circ}\text{C}$ 

Suitable storage materials : Original containers.

Higher temperatures and humidity will reduce the shelf life of the product and may cause the powder to form lumps. The powder will also be difficult to mix into a paste.

Under normal conditions (21°C) a shelf life of 12 months or more is possible.

7.3 Specific end use(s) As per section 1.2

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1 Control parameters

# 8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

Dust	TWA STEL	mg/m³ 10 4	ppm inhalable respirable	Note (EH40 UK) OES 8 hr (EH40 UK)
	TWA STEL			(EH40 UK) (EH40 UK)
	TWA STEL			(EH40 UK) (EH40 UK)

8.1.2 Biological limit value Not available8.1.3 PNECs and DNELs Not available

## 8.2 Exposure Controls

**8.2.1** Appropriate engineering controls: Effective exhaust ventilation system

## **8.2.2 Personal Protective Equipment:**

Eye/face Tightly fitting safety goggles (e.g. EN166)

Protection

Hand

Skin Protection/ Gloves: Chemical resistant gloves (e.g. EN374) Butyl rubber: 0.7 mm

coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE

manufacturer. Replace immediately if signs of degradation are observed.

Other Wear closed work clothing.

Respiratory In the case of insufficient ventilation or severe dusts

Protection Cartridge: e.g. EN143 Type P-S (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

#### 8.2.3 Environmental exposure controls

No special environmental precautions required

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER N° X52** 

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1 information on basic physical and chemical properties

APPEARANCE	Fine powder	COLOUR	Cream
Odour	None	ODOUR THRESHOLD ppm	Not Available
pH Value Melting Point/Freezing pt INITIAL BOILING POINT/RANGE FLASHPOINT °C	2.2 Not applicable Not applicable Not applicable	RELATIVE DENSITY SOLUBILITY IN WATER @ 20°C PARTITION COEFFICIENT (n-octanol/water)	2.5 g/ml <150 g/l Not available
EVAPORATION RATE FLAMMABILITY (SOLID/GAS) UPPER EXPLOSIVE LIMIT LOWER EXPLOSIVE LIMIT VAPOUR PRESSURE VAPOUR DENSITY (AIR=1)	Not applicable Not applicable Not Available Not Available Not applicable Not applicable	AUTO IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE °C VISCOSITY mPa.s @ 25°C EXPLOSIVE PROPERTIES OXIDIZING PROPERTIES	Not available Not available Not applicable Not available Not oxidising

## 9.2 Other information

#### **SECTION 10: STABILITY AND REACTIVITY**

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical Stability	Stable under recommended storage and handling conditions.
10.3	Possibility of	No dangerous reaction known under conditions of normal use
	<b>Hazardous reactions</b>	
10.4	<b>Conditions to Avoid</b>	No decomposition if stored and applied as directed.
10.5	Incompatible	Acids
	materials	
10.6	Hazardous	No hazardous decomposition products if stored and handled as
	Decomposition	prescribed/ indicated.
	Products.	

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects of the mixture

Acute toxicity	Contains components that are hazardous by the following routes
	: skin, eye, inhalation.

LD 50 ORAL TOXICITY RATS	mg/kg
LD <sub>50</sub> DERMAL TOXICITY RATS	ml/kg
LC 50 INHL TOXICITY IN RATS	mg/kg
LD 50 ORAL TOXICITY RATS	mg/kg
LD <sub>50</sub> DERMAL TOXICITY RABBITS	mg/kg
LC 50 INHL TOXICITY IN RATS	mg/kg

Skin corrosion/ irritation	Irritating
Serious eye damage / irritation	Irritating
Respiratory or skin sensitisation	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

Reproductive toxicity
STOT SE (SINGLE exposure)
STOT RE (REPEATED exposure)
Aspiration hazard

Not classified
Not classified
Not classified

## 11.2 Other information

Skin sensitisation might occur in people with hypersensitive skin.

#### **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1 Toxicity

LL <sub>50</sub> Fish EC <sub>50</sub> Invertibrates EL <sub>50</sub> Algae	(96 hr) (48 hr) (72hr)	mg/l mg/l mg/l	Daphnia magna Selenastrum capricornutum
LL <sub>50</sub> Fish	(96 hr)	mg/l	Lepomis macrochirus
EC <sub>50</sub> Invertibrates	(48 hr)	mg/l	Daphnia magna
EL <sub>50</sub> Algae	(72hr)	mg/l	Selenastrum capricornutum

Micro organisms/ effect upon activated sludge

EC<sub>50</sub> Bacteria (3.0 hr) mg/l Activated sludge, domestic

# **12.2** Persistance and Not bio degradable

degradability

## **12.3** Bioaccumulative potential Not available

# **12.4 Mobility in soil** Sinks in water. A small percentage (<15%) is water

soluble. If the product enters soil, it will be mobile and

may contaminate groundwater.

# 12.5 Results of PBT and vPvB

assessment

PBT: This mixture contains no substances considered

as PBT

vPvB: This mixture contains no substances considered

as vPvB

## 12.6 Other adverse effects

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

#### **SECTION 13: DISPOSAL CONSIDERATION**

#### 13.1 Waste treatment methods

The preparation must be disposed of by special means. Dispose by landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

### 13.2 Additional information

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

Dispose of contents/ container according to the end user disposal procedure (P501)

#### **SECTION 14: TRANSPORT INFORMATION**

#### **14.1 UN number** NOT CLASSIFIED

ADR

**RID** 

**IMDG** 

**IATA** 

ADN

# **14.2 Proper shipping name** NOT CLASSIFIED

ADR

**RID** 

**IMDG** 

IATA

ADN

## 14.3 Transport Hazard Class NOT CLASSIFIED

**ADR** 

**RID** 

**IMDG** 

**IATA** 

ADN

# 14.4 Packing Group NOT CLASSIFIED

**ADR** 

RID

**IMDG** 

IATA

ADN

#### 14.5 Environmental hazards NOT CLASSIFIED

ADR

RID

**IMDG** 

**IATA** 

ADN

#### 14.6 Special Precautions for user

Not classified as dangerous in the meaning of transport regulations

Date Revised : 18.02.2022 Revision : 05

Product : **ELECTROTEMP CEMENT POWDER Nº X52** 

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

#### **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the mixture

**EU** Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793193 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Employment restrictions: Observe employment restrictions for young people, for child bearing mothers/ nursing and for women of child-bearing age.

#### 15.2 Chemical Safety Assessment

Exposure scenarios are not required for this mixture because it is not classified as dangerous according to Directive 67/548/EEC and assessed to be not PBT/vPvB. No risk management measures as defined by REACH have been identified.

#### **SECTION 16: OTHER INFORMATION \***

\* SECTIONS REVISED 1 Supercedes date 31.10.2018

Reference made to UK/EU REACH

Legend

PBT Persistent, Bioaccumulative and Toxic VPVB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

Training advice General industrial hygiene practice.

Manual handling

Further information

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to it's accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.