

C-Bond

by

Glassbond

Technical Data Sheet

L401 – Adhesive Debonder

Characteristics

- ❑ Used for cleaning cured and uncured material
- ❑ Can be used for debonding skin
- ❑ Will soften thick deposits of cured material
- ❑ Optimised for use with C-Bond cyanoacrylates

Recommended For

Small areas of cured material present on substrates such as steel, plastic, wood, glass and rubber

Description

Glassbond Adhesive Debonder L401 can be used to clean areas of uncured C-Bond Adhesive and also to remove small areas of cured material. In addition, it will soften thick deposits of cured cyanoacrylate over time. Adhesive Debonder L401 is also suitable for debonding skin. Care must be taken to avoid contact with eyes and mouth area when using for this specific application.

Physical properties

Base	Polypropylene carbonate
Appearance	Clear
Specific gravity (at 20°C)	-1.2
Flash point	<68°C
Viscosity	-2
Shelf life	12 months

Application/Instructions

FOR BONDED ADHESIVE – For best results, apply L401 with a brush to glue line and leave for 30 seconds. Repeat if necessary. Bond line will be released. Remove excess by wiping with a clean cloth.

FOR BONDED SKIN – For best results, apply L401 with a brush to glue line and leave for 30 seconds. Repeat if necessary. Bond line will be released. Wash area immediately with warm soapy water and apply moisturising cream if necessary.

Under no circumstances should L401 be used on areas of broken/sensitive skin in addition to ensuring there is no contact with eyes and mouth area.

Packaging

This material is supplied in various types and sizes of containers. Please contact Glassbond's sales department for further details (sales@glassbond.co.uk).

Shelf Life

Glassbond Adhesive Debonder L401 has a shelf life of 12 months when stored in unopened, tightly sealed containers in a cool, dry location, out of direct sunlight. If there is doubt as to the quality of the material, consult Glassbond.

Caution

Never use on areas of the body as specified previously in this data sheet.

Consult the Material Safety Data Sheets and container label caution statements for any hazards in handling this material.

Warranty

We warrant that our goods will conform to the description contained in the order and that we have good title to all goods sold. WE GIVE NO WARRANTY, WHETHER OF MERCHANTABILITY, FITNESS FOR PURPOSE OR OTHERWISE, EXPRESS OR IMPLIED, OTHER THAN AS EXPRESSLY SET FORTH HEREIN. Users shall determine the suitability of the product for intended application before using.