# SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : GLASSBOND P165/M PASTE

REACH notes : Mixture- Substances contained in this product that are

not classified as hazardous have been/will be registered for

REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : Lamp capping adhesive

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd

West Side Industrial Estate

Jackson Street St. Helens

Merseyside WA9 3AT United Kingdom

Telephone +44(0)1744730334Fax +44(0)1744451661

Email technical@glassbond.co.uk

**1.4** Emergency telephone +44(0)1744 730334

**number** (GMT, English spoken, Mon-Friday; 08.30-16.30)

#### **SECTION 2: HAZARDS IDENTIFICATION \***

# 2.1 Classification of the mixture: calculation method

**2.1.1** Regulation (EC) No. 1272/2008(CLP)

Physical/Chemical Not Classified

Human health May cause an allergic skin reaction. Skin Sens. 1

Environmental Not classified

2.2 Label elements According to Regulation (EC) No. 1272/2008(CLP)

Hazard pictogram(s)

GHS07

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

SIGNAL WORD(S) WARNING

HAZARD H317 May cause an allergic skin reaction.

Skin Sens. 1

STATEMENT(S)

PRECAUTIONARY P261 Avoid breathing dust/fume

STATEMENT(S) P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (avoid skin contact)

**2.3 Other** Code EUH208 'Contains colophony. May produce an allergic reaction.

Hazards

PBT: This mixture contains no substances considered as PBT

vPvB: This mixture contains no substances considered as vPvB

**2.4** Additional For full text of H/P phrases see section 16 if not written out in full

**information** above.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*

**3.1** Substances (This product is a mixture according to EU legislation)

**3.2** Mixture of Synthetic resin dissolved in industrial denatured spirits, containing inert fillers.

Hazardous	%	CAS N°	EC N°	REACH N°	CPL
ingredient	w/w				EC 1272/2008
Hexamine	1-2	100-97-0	202-905-8	Not available	H228: Flammable solid. H317: May cause an allergic skin reaction.
Rosin	6-8	8050-09-7	232-475-7	01- 2119480418 -32-0004	H317 - May cause an allergic skin reaction. Skin Sens. 1
Industrial denatured spirit	5-7	64-17-5	200-578-6	Ethanol mixture contains 5% methanol	H225 Highly flammable Liquid and Vapour H371 May cause damage to organs if swallowed in contact with skin and via inhalation

# 3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

## **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures

General advice 
Immediately remove contaminated clothing, take care not to contaminate

unaffected areas.

Inhalation Contains component irritating by inhalation. Move the exposed person to fresh

air. Seek medical attention.

Eyes Rinse immediately with running water for at least 15 minutes holding the eyelid

open; consult an eye specialist.

Skin Wash thoroughly with water and soap

If skin irritation or rash occurs get medical attention (P333+P313)

Ingestion Immediately rinse the mouth with water and drink plenty of water. Obtain

medical attention immediately, show this safety data sheet.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms Eye contact- May cause temporary eye irritation.

Risks No information available

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

# **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 Extinguishing media:

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and

extinguish flames.

Unsuitable: High pressure water jet

# 5.2 Special hazards arising from the mixture

Harmful vapours. Thermal decomposition or burning may release toxic oxides of nitrogen and other toxic gases.

#### **5.3** Advice for fire fighters

Use full protective clothing and self-contained breathing apparatus.

**Further information**: The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal Precautions, protective equipment and emergency procedures

Use personal protective clothing. Eliminate sources of ignition

## 6.2 Environmental Precautions

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

# 6.3 Methods and material for containment and cleaning up

Collect spillage by sweeping or scraping up. keep in suitable closed container for disposal.

## 6.4 Reference to other sections

For personal protection see section 8 and disposal section 13

: 19/07/2023 Revision: 3 Date Revised

Product : GLASSBOND P165/M PASTE

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling

Advice on safe handling Ensure thorough ventilation of stores and work areas. For PPE

> see section 8. Contaminated clothing should not be allowed out of the workplace (P272). Wash contaminated clothing

before reuse (P363)

Advice on protection against fire and explosion Sources of ignition should be kept well clear. Take

precautionary measures against static discharges if delivered

in plastic packaging.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. The paste should be stored under cover, in a wellventilated, cool, dry place and away from direct sunlight, heat or sources of ignition.

Protect from temperatures below: minus 5 °C Protect from temperatures above: 35 °C Suitable storage materials: Original containers.

Higher temperatures and humidity will reduce the shelf life of the product. Under

normal conditions (21°C) a shelf life of 8 weeks or more is possible.

#### 7.3 Specific end use(s) As per section 1.2

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 **Control parameters**

# 8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

		mg/m³	ppm	Note
Industrial methylated spirits (IMS)	TWA	1920	1000	(EH40 UK) OES 8 hr
, ,	STEL			(EH40 UK)
	TWA			(EH40 UK)
	STEL			(EH40 UK)
	TWA			(EH40 UK)
	STEL			(EH40 UK)

8.1.2 **Biological limit value** Not available **PNECs and DNELs** Not available 8.1.3

#### 8.2 **Exposure Controls**

Appropriate engineering controls: Effective exhaust ventilation system 8.2.1

#### 8.2.2 **Personal Protective Equipment:**

Eye/face Tightly fitting safety goggles (e.g., EN166)

Protection

Hand

Other

Gloves: Chemical resistant gloves (e.g., EN374) Butyl rubber: 0.7 mm Skin Protection/

coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE manufacturer. Replace immediately if signs of degradation are observed.

Wear closed work clothing.

Respiratory Chemical cartridge if there is a risk of breathing vapours

Protection Cartridge: e.g., EN14387 Type A (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

#### **Environmental exposure controls** 8.2.3

No special environmental precautions required

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1 Information on basic physical and chemical properties

Appearance Odour	Thick Paste alcoholic	COLOUR ODOUR THRESHOLD ppm	Green Not Available
pH Value Melting Point/freezing pt INITIAL BOILING POINT/RANGE FLASHPOINT °C	Not available Not applicable 78°C (IMS) Not applicable	RELATIVE DENSITY SOLUBILITY IN WATER PARTITION COEFFICIENT (n-octanol/water)	1.9 g/ml <1% soluble 0.32 (IMS)
EVAPORATION RATE FLAMMABILITY (SOLID/GAS) UPPER EXPLOSIVE LIMIT LOWER EXPLOSIVE LIMIT VAPOUR PRESSURE VAPOUR DENSITY (AIR=1)	Not applicable Not applicable Not Available >1.3 % (IMS) Not applicable 1.6 (IMS)	AUTO IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE °C VISCOSITY mPa.s @ 25°C EXPLOSIVE PROPERTIES OXIDIZING PROPERTIES	Not available Not available Not applicable Not available Not oxidising

#### 9.2 Other information

Partially soluble in alcohols

#### SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical Stability	Stable under recommended storage and handling conditions.
10.3	Possibility of	No dangerous reaction known under conditions of normal use
	<b>Hazardous reactions</b>	
10.4	<b>Conditions to Avoid</b>	No decomposition if stored and applied as directed.
10.5	Incompatible	Acids, strong oxidising agents
	materials	
10.6	Hazardous	No hazardous decomposition products if stored and handled as
	Decomposition	prescribed/ indicated.
	Products	Fire creates oxides of carbon and nitrogen, formaldehyde.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects of the mixture

Acute toxicity		•	at are hazardous by the following		
	routes: skin, eye, inhalation and ingestion.				
LD 50 ORAL TOXICITY RATS	9200	mg/kg	Hexamine		
LD <sub>50</sub> DERMAL TOXICITY RATS	2000	mg/kg	Hexamine		
LC 50 INHL TOXICITY IN RATS	7600	mg/kg	Rosin		
LD 50 ORAL TOXICITY RATS	>2800	mg/kg	Rosin		
LD <sub>50</sub> DERMAL TOXICITY RABBITS	>2000	mg/kg	Rosin		
LD 50 ORAL TOXICITY RATS	6200-17800	mg/kg	Industrial methylated spirits		
LD <sub>50</sub> DERMAL TOXICITY RABBITS	>20000	mg/kg	Industrial methylated spirits		
LC 50 INHL TOXICITY IN RATS	>20000	mg/lt/4hr	Industrial methylated spirits		

Skin corrosion/ irritation Serious eye damage/ irritation Respiratory or skin sensitisation

Irritating

May cause irritation

The product contains Hexamine and rosin which are skin sensitising. Materials of this type are known to cause respiratory allergy in people.

Not classified Not classified

Germ cell mutagenicity Carcinogenicity

Print date 19/07/2023 5/8 SDS –P165/M July 2023

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

Reproductive toxicity
STOT SE (SINGLE exposure)
STOT RE (REPEATED exposure)
Aspiration hazard

Not classified
Not classified
Not classified

#### 11.2 Other information

Skin sensitisation might occur in people with hypersensitive skin.

#### **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1 Toxicity

LL <sub>50</sub> Fish	(96 hr)	<10 (rosin)	mg/l	Lepomis macrochirus
EC 50 Invertebrates	(48 hr)		mg/l	Daphnia magna
EL 50 Algae	(72hr)	>1000 (rosin)	mg/l	Selenastrum capricornutum
LL 50 Fish	(96 hr)	41000 (hexamine)	mg/l	Lepomis macrochirus
EC 50 Invertebrates	(48 hr)	36000 (hexamine)	mg/l	Daphnia magna
EL 50 Algae	(72hr)		mg/l	Selenastrum capricornutum

Microorganisms/ effect upon activated sludge

EC<sub>50</sub> Bacteria (3.0 hr) > 10000(rosin) mg/l Activated sludge, domestic

**12.2** Persistence and Organic resin components are not readily

**degradability** biodegradable.

Solvent is readily biodegradable

**12.3** Bioaccumulative potential Not available

**12.4 Mobility in soil** Sinks in water. A small percentage (<10%) is water

soluble. If the product enters soil, it will be mobile and

may contaminate groundwater.

12.5 Results of PBT and vPvB PBT: This mixture contains no substances considered as

assessment

PBT

vPvB: This mixture contains no substances considered

as vPvB

# 12.6 Other adverse effects

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

#### **SECTION 13: DISPOSAL CONSIDERATION**

## 13.1 Waste treatment methods

The preparation must be disposed of by special means. Dispose by incineration or landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

#### 13.2 Additional information

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

Dispose of contents/ container according to the end user disposal procedure (P501)

## **SECTION 14: TRANSPORT INFORMATION**

# **14.1 UN number** NOT CLASSIFIED

ADR

RID

**IMDG** 

IATA

ADN

# **14.2 Proper shipping name** NOT CLASSIFIED

**ADR** 

RID

**IMDG** 

IATA

ADN

# 14.3 Transport Hazard Class NOT CLASSIFIED

**ADR** 

**RID** 

**IMDG** 

**IATA** 

ADN

# 14.4 Packing Group NOT CLASSIFIED

**ADR** 

RID

**IMDG** 

**IATA** 

ADN

# 14.5 Environmental hazards NOT CLASSIFIED

ADR

**RID** 

**IMDG** 

IATA

ADN

## 14.6 Special Precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage

Date Revised : 19/07/2023 Revision : 3

Product : GLASSBOND P165/M PASTE

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

#### **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the mixture

**EU** Legislation

Commission Regulation (EC) No 474/2014 of  $8^{\rm th}$  May 2014 amending Annex XVII to Regulation (EC) No 1907/2006

Commission Regulation (EC) No 944/2013 of  $2^{nd}$  October 2013 ( $5^{th}$  ATP) amending Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

Waste Framework Directive 2008/98/EC

Employment restrictions: Observe employment restrictions for young people, for child bearing mothers/ nursing and for women of child-bearing age.

# 15.2 Chemical Safety Assessment

Assessed to be not PBT/vPvB

## **SECTION 16: OTHER INFORMATION \***

\* SECTIONS REVISED 2 Supersedes date 28/09/2017

Removal of section 2.1.2

Legend

PBT Persistent, Bioaccumulative and Toxic VPVB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

H228 Flammable solid.

H317 May cause an allergic skin reaction. H225 Highly flammable Liquid and Vapour

H371 May cause damage to organs if swallowed in contact with skin and via

inhalation

Training advice General industrial hygiene practice.

Manual handling

Further information

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.