SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : GLASSBOND SAUEREISEN SEALING CEMENT Nº 33S

REACH notes : Mixture- Substances contained in this product that are

not classified as hazardous have been/will be registered for

UK/EU REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : High temperature adhesive and sealant

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd

West Side Industrial Estate

Jackson Street St. Helens

Merseyside WA9 3AT United Kingdom

Telephone +44(0)1744 730334 Fax +44(0)1744 451661 Email technical@glassbond.co.uk

1.4 Emergency telephone +44(0)1744 730334

number (GMT, English spoken, Mon-Friday; 08.30-16.30)

SECTION 2: HAZARDS IDENTIFICATION*

2.1 Classification of the mixture: calculation method

2.1.1 Regulation (EC) No. 1272/2008(CLP)

Physical/Chemical Not Classified

Human health STOT RE 2 (inhalation), Eye damage 1, Skin irritant 2

Acute toxicity 4 (inhalation dermal and oral),

Environmental NOT CLASSIFIED

2.2 Label elements According to Regulation (EC) No. 1272/2008(CLP)



Print date 17/07/2023



STOT RE 2 (inhalation)

GHS08 GHS05

Date Revised : 12/07/2023 Revision : 19

Product : **SEALING CEMENT N°33S**

SIGNAL WORD (S)		Danger		
HAZARD STATEMENT(S)	H373 H315 H318 H332 H312 H302	Causes damage to lungs through prolonged or rexposure via inhalation Causes skin irritation Causes serious eye damage Harmful if inhaled Harmful in contact with skin Harmful if swallowed	Cat 2 Cat 1 Acute Tox 4 Acute Tox 4 Acute Tox 4	
PRECAUTIONARY STATEMENT(S)	P260 P280 P305 + P351 + P338 P310	Do not breathe dust Wear protective gloves /protective clothing/eye protection/face protection IF IN EYES: rinse cautiously with water for several minutes. Remo contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTRE or doctor		

2.3 Other Hazards

PBT: This mixture contains no substances considered as PBT

vPvB: This mixture contains no substances considered as vPvB

2.4 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS*

- **3.1** Substances (This product is a mixture according to EU legislation)
- **3.2** Mixture of inorganic powders

Hazardous ingredient	% w/w	CAS Nº	EC Nº	REACH Nº	CPL EC 1272/2008
Silica	>70	14808-60-7	238-878-4	Exempted	H373: STOT RE 2
Sodium silicate	<20	1344-09-8	215-687-4	01-2119448725- 31	H335: STOT SE 3 (inhalation) H318: Eye irritant 1 H315: Skin Irritant 2
Sodium silico fluoride	3≤10	16893-85-9	240-934-8	01-2119519245- 43-0002	H331: Acute Tox 3 (inhalation) H311: Acute Tox 3 (dermal) H301: Acute Tox 3 (oral)

3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General Take off contaminated clothing and wash before re-use (P362).

advice Take care not to contaminate unaffected areas.

Inhalation IF INHALED remove victim to fresh air and keep at rest in a position comfortable for

breathing. (P304+P340)

Eyes IF IN EYES rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. (P305 + P351 + P338) If eye irritation persists: Get medical attention (P337+P313)

Skin Wash hands thoroughly after handling (P264)

If skin irritation or rash occurs get medical attention (P333+P313)

Ingestion IF SWALLOWED: Rinse mouth (P330). Call a POISON CENTRE or doctor if you feel

unwell (P301+P312). Show this safety data sheet.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Eye contact- May cause temporary eye irritation.

Risks No information available

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media:

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and

extinguish flames for surrounding materials.

Unsuitable: High pressure water jet.

5.2 Special hazards arising from the mixture

The powder will not burn but the packaging is combustible. When heated to decomposition it emits toxic and corrosive fumes of hydrogen fluoride.

5.3 Advice for fire fighters

Use full protective clothing and self-contained breathing apparatus.

Further information: The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, protective equipment and emergency procedures

Use personal protective clothing.

6.2 Environmental Precautions

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

6.3 Methods and material for containment and cleaning up

Collect spillage by sweeping or industrial vacuum cleaner. keep in suitable closed container for disposal

6.4 Reference to other sections

For personal protection see section 8 and disposal section 13

Date Revised : 12/07/2023 Revision : 19

Product : **SEALING CEMENT N°33S**

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe Avoid the formation and deposition of dust. Use only outdoors or in a well-ventilated area (P271). For PPE see

section 8. Take off contaminated clothing and wash before

re-use (P362).

Advice on protection Normal measures for preventive fire protection

against fire and explosion Take precautionary measures against static discharge

if using plastic packaging.

7.2 Conditions for safe storage, including any incompatibilities

Store locked up (P405). Store in a well-ventilated place. Keep containers tightly closed.

(P403+P233) Keep cool and dry, away from direct sunlight or heat.

Protect from temperatures below: Not applicable

Protect from temperatures above: 40 °C

Suitable storage materials: Original containers.

Higher temperatures and humidity will reduce the shelf life of the product and may cause the powder to form lumps. The powder will also be difficult to mix into a paste.

Under normal conditions (21°C) a shelf life of 12 months or more is possible.

7.3 Specific end use(s) As per section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

		mg/m³	ppm	Note
Silica crystalline	TWA	-	inhalable	(EH40 UK) OES 8 hr
	TWA	0.3	respirable	(EH40 UK)
Silica crystalline	TLV-TWA	0.1	respirable	(ACIGH)
	STEL	-		(EH40 UK)
Sodium silicate	TWA	2.0		recommended
Sodium silicofluoride	TWA	2.5		OSHA
	STEL	-		

8.1.2 Biological limit value Not available8.1.3 PNECs and DNELs Not available

8.2 Exposure Controls

8.2.1 Appropriate engineering controls: Effective exhaust ventilation system

8.2.2 Personal Protective Equipment:

Eye/face Tightly fitting safety goggles (e.g., EN166)

Protection

Skin Protection/ Gloves: Chemical resistant gloves (e.g., EN374) Butyl rubber: 0.7 mm

Hand coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE

manufacturer. Replace immediately if signs of degradation are observed.

Other Wear closed work clothing.

Respiratory In the case of insufficient ventilation or severe dusts

Protection Cartridge: e.g., EN143 Type P-S (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

8.2.3 Environmental exposure controls

Local exhaust ventilation and take precautionary measures against static discharge.

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 information on basic physical and chemical properties

Appearance Odour	Fine powder None	COLOUR ODOUR THRESHOLD ppm	Cream Not Available
pH VALUE MELTING POINT/FREEZING PT INITIAL BOILING POINT/RANGE FLASHPOINT °C	13 Not applicable Not applicable Not applicable	RELATIVE DENSITY SOLUBILITY IN WATER @ 20°C PARTITION COEFFICIENT (n-octanol/water)	2.7 g/ml 30 g/100g Not available
EVAPORATION RATE FLAMMABILITY (SOLID/GAS) UPPER EXPLOSIVE LIMIT LOWER EXPLOSIVE LIMIT VAPOUR PRESSURE VAPOUR DENSITY (AIR=1)	Not applicable Not applicable Not Available Not Available Not applicable Not applicable	AUTO IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE °C VISCOSITY mPa.s @ 25°C EXPLOSIVE PROPERTIES OXIDIZING PROPERTIES	Not available Not available Not applicable Not available Not oxidising

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1	Reactivity	Stable under normal conditions.
10.2	Chemical Stability	Stable under recommended storage and handling conditions.
10.3	Possibility of	No dangerous reaction known under conditions of normal use
	Hazardous reactions	
10.4	Conditions to Avoid	No decomposition if stored and applied as directed.
10.5	Incompatible	Incompatible with strong acids, alkaline materials, iron
	materials	containing materials. It may react with strong mineral acids
		to liberate hydrogen fluoride or hydrofluoric acid which are
		highly toxic and corrosive.
10.6	Hazardous	No hazardous decomposition products if stored and handled as
	Decomposition	prescribed/ indicated.
	Products	

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects of the mixture

Acute toxicity	Contains co	omponents that	t are	hazardous	by	the	following
	routes: skin	, eye, inhalation	١.				
LD 50 ORAL TOXICITY MOUSE	70	mg/kg		Sodium silid	coflu	oride	<u> </u>
LD 50 ORAL TOXICITY IN RATS	125	mg/kg		Sodium silic	oflu	oride	!
LD ₅₀ DERMAL TOXICITY RABBITS	500	mg/kg		Sodium silic	oflu	oride	!
LC 50 INHL TOXICITY IN RATS		mg/kg					
LD ₅₀ DERMAL TOXICITY RABBITS		mg/kg					
LC 50 ORAL TOXICITY IN RATS	3400	mg/kg		Sodium s	silica	te	
LD ₅₀ DERMAL TOXICITY RATS	>2000	mg/kg		Sodium s	ilica	te	

Skin corrosion/ irritation
Serious eye damage/ irritation
Respiratory or skin sensitisation
Germ cell mutagenicity
Carcinogenicity

Irritating Serious eye damage

Not classified Not classified

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis cause by deposition in the lungs of fine respirable particles of crystalline silica.

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

Reproductive toxicityNot classifiedSpecific Target Organ Toxicity (Repeated Exposure)STOT RE2Specific Target Organ Toxicity (Single Exposure)Not classifiedAspiration hazardNot classified

11.2 Other information

In 1997, IARC (International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. Continuous or intermittent exposure to inorganic fluorides can lead to appreciable accumulation of fluoride in bone, and, to development of osteosclerosis and other bone changes.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

•		sodium silicate		
LL ₅₀ Fish	(96 hr)	1108	mg/l	Brachydanio rerio
EC 50 Invertebrates	(48 hr)	1700	mg/l	Daphnia magna
EL 50 Algae	(72hr)		mg/l	Selenastrum capricornutum
		Sodium silicofluoride		
LL ₅₀ Fish	(96 hr)	37.5	mg/l	Lepomis macrochirus
EC 50 Invertebrates	(48 hr)	35.4	mg/l	Daphnia magna
EL 50 Algae	(72hr)	18.5	mg/l	Selenastrum capricornutum

Microorganisms/ effect upon activated sludge

EC₅₀ Bacteria (3.0 hr) mg/l Activated sludge, domestic

12.2 Persistence and Not biodegradable degradability

12.3 Bioaccumulative potential Not available

12.4 Mobility in soil Sinks in water. A small percentage (~30%) is water

soluble. If the product enters soil, it will be mobile and

may contaminate groundwater.

12.5 Results of PBT and vPvB PBT: This mixture contains no substances considered as

assessment PBT

vPvB: This mixture contains no substances considered

as vPvB

12.6 Other adverse effects

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

SECTION 13: DISPOSAL CONSIDERATION

13.1 Waste treatment methods

The preparation must be disposed of by special means. Dispose by landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

13.2 Additional information

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

Dispose of contents/ container according to the end user disposal procedure (P501)

SECTION 14: TRANSPORT INFORMATION

14.1 UN number NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.2 Proper shipping name NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.3 Transport Hazard Class NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.4 Packing Group NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.5 Environmental hazards NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.6 Special Precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in case of accident or spill

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code Not applicable

Print date 17/07/2023 7/8 SDS – Sauereisen No 33S July 2023

Date Revised : 12/07/2023 Revision : 19

Product : SEALING CEMENT N°33S

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the mixture

EU legislation Regulation (EC) No 474/2014 of 8 May 2014 amending Annex XVII to Regulation (EC) No 1907/2006

Regulation (EC) No 944/2013 of 2 October 2013 (5th ATP) amending Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

Directive 2008/98 / EC waste framework

Employment restrictions: Observe employment restrictions for young mothers to procreate / nursing and women of childbearing age.

15.2 Chemical Safety Assessment

Assessed to be not PBT/ vPvB.

SECTION 16: OTHER INFORMATION *

* SECTIONS REVISED 2 Supersedes date 02/03/2022

Removal of section 2.1.2

Legend

PBT Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

H301 Toxic if swallowed

H311 Toxic in contact with skin Toxic by inhalation

H335 May cause respiratory irritation

Training advice General industrial hygiene practice. Do not eat, drink or smoke when

using this product (P270)

Manual handling

Further information

Print date

17/07/2023

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.