SAFETY DATA SHEET



Safety Data Sheet according to regulation (EC) N°1907/2006, 1272/2008(CLP) & 453/2010

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/ MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product name : GLASSBOND SAUEREISEN ELECTRIC RESISTOR CEMENT N°78/3

REACH notes : Mixture- Substances contained in this product that are

not classified as hazardous have been/will be registered for

UK/EU REACH at the appropriate time.

1.2 Relevant identified uses of the mixture and uses advised against.

Identified use : High temperature adhesive and sealant

Uses advised against : No other uses

1.3 Details of the supplier of the safety data sheet

Company identification Glassbond (NW) Ltd

West Side Industrial Estate

Jackson Street St. Helens

Merseyside WA9 3AT United Kingdom

Telephone +44(0)1744 730334 Fax +44(0)1744 451661 Email technical@glassbond.co.uk

1.4 Emergency telephone +44(0)1744 730334

number (GMT, English spoken, Mon-Friday; 08.30-16.30)

SECTION 2: HAZARDS IDENTIFICATION*

2.1 Classification of the mixture: calculation method

2.1.1 Regulation (EC) No. 1272/2008(CLP)

Physical/Chemical NOT CLASSIFIED

Human health STOT RE 2 (inhalation), Eye damage 1, Skin Irritant 2

Environmental Not classified

GS05

2.2 Label elements According to Regulation (EC) No. 1272/2008(CLP)

1/8

STOT RE 2

Print date 17/07/2023

GHS08

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SIGNAL WORD (S)			DANGER		
HAZARD STATEMENT(S)	H373		Causes damage to lungs through prolonged or repeat via inhalation	ungs through prolonged or repeated exposure	
` ,	H315		Causes skin irritation.	Cat 2	
	H318		Causes serious eye damage	Cat 1	
PRECAUTIONARY STATEMENT(S)	P260 P280 P305 P351 P338 P310	+++	Do not breathe dust Wear protective gloves /protective clothing/eye prote protection IF IN EYES rinse cautiously with water for several minutes. F lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTRE or doctor	•	

2.3 Other Hazards

PBT: This mixture contains no substances considered as PBT vPvB: This mixture contains no substances considered as vPvB

2.4 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS*

- **3.1** Substances (This product is a mixture according to EU legislation)
- **3.2** Mixture of inorganic powders

Hazardous ingredient	% w/w	CAS Nº	EC Nº	REACH N°	CPL EC 1272/2008
Silica powder	40-50	14808-60-7	238-878-4	Exempted	H373: STOT RE 2
Sodium silicate	10-15	1344-09-8	215-687-4	01-2119448725- 31	H335: STOT SE 3 (inhalation) H318: Eye damage 1 H315: Skin Irritant 2
					_

3.3 Additional information

For full text of H/P phrases see section 16 if not written out in full above.

2/8

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General Take off contaminated clothing and wash before re-use (P362), take care not to

advice contaminate unaffected areas.

Inhalation IF INHALED remove victim to fresh air and keep at rest in a position comfortable for

breathing. (P304+P340)

Eyes IF IN EYES rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. (P305 + P351 + P338) If eye irritation persists: Get medical attention (P337+P313)

Skin IF ON SKIN wash exposed areas thoroughly after handling (P264)

If skin irritation or rash occurs get medical attention (P332+P313)

Ingestion IF SWALLOWED: Rinse mouth. Do not induce vomiting (P301+P330+P331). Obtain

medical attention immediately, show this safety data sheet.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Eye contact- May cause serious eye damage (highly alkaline)

Risks No information available

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

SECTION 5: FIRE FIGHTING MEASURES

5.1 Extinguishing media:

Suitable: CO2 or dry chemical spray, water spray may help to reduce the temperature and

extinguish flames for surrounding materials.

Unsuitable: High pressure water jet.

5.2 Special hazards arising from the mixture

The powder will not burn but the packaging is combustible.

5.3 Advice for fire fighters

Use full protective clothing and self-contained breathing apparatus.

Further information: The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing media must be disposed of in accordance with official regulation.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, protective equipment and emergency procedures

3/8

Use personal protective clothing.

6.2 Environmental Precautions

Prevent contamination of soil, drains and surface waters. Do not discharge contaminated water/ fire-fighting water into drains/ surface water/ groundwater.

6.3 Methods and material for containment and cleaning up

Collect spillage by sweeping or industrial vacuum cleaner. keep in suitable closed container for disposal

6.4 Reference to other sections

17/07/2023

Print date

For personal protection see section 8 and disposal section 13

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT N°78/3**

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe Avoid the formation and deposition of dust. Use only outdoors or in a well-ventilated area (P271). For PPE see section 8.

Wash contaminated clothing before reuse (P363)

Advice on protection Normal measures for preventive fire protection

against fire and explosion Take precautionary measures against static discharge

if using plastic packaging

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Store locked up (P405), under cover, in a well ventilated,

cool, dry place and away from direct sunlight or heat.

Protect from temperatures below: Not applicable

Protect from temperatures above: 40 °C

Suitable storage materials: Original containers.

Higher temperatures and humidity will reduce the shelf life of the product and may cause the powder to form lumps. The powder will also be difficult to mix into a paste.

Under normal conditions (21°C) a shelf life of 12 months or more is possible.

7.3 Specific end use(s) As per section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits: OEL (Occupational Exposure Standard OES)

		mg/m³	ppm	Note
Silica crystalline	TWA	-	inhalable	(EH40 UK) OES 8 hr
	TWA	0.3	respirable	(EH40 UK)
Silica crystalline	TLV-TWA	0.1	respirable	(ACIGH)
	STEL	-		
Sodium silicate	TWA	2.0		recommended
	TWA	-		
	STEL	-		

8.1.2 Biological limit value Not available **8.1.3 PNECs and DNELs** Not available

8.2 Exposure Controls

8.2.1 Appropriate engineering controls: Effective exhaust ventilation system

8.2.2 Personal Protective Equipment:

Eye/face Tightly fitting safety goggles (e.g., EN166)

Protection

Hand

Skin Protection/ Gloves: Chemical resistant gloves (e.g., EN374) Butyl rubber: 0.7 mm

coating thickness. Nitrile rubber: 0.4 mm coating thickness. Check with PPE

manufacturer. Replace immediately if signs of degradation are observed.

Other Wear closed work clothing.

Respiratory In the case of insufficient ventilation or severe dusts

Protection Cartridge: e.g., EN143 Type P-S (check with PPE manufacturer)

Hygiene measures General industrial hygiene practice

8.2.3 Environmental exposure controls

Local exhaust ventilation and take precautionary measures against static discharge.

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 information on basic physical and chemical properties

Appearance Odour	Fine powder None	COLOUR ODOUR THRESHOLD ppm	Cream Not Available
pH Value Melting Point/freezing pt INITIAL BOILING POINT/RANGE FLASHPOINT °C	11-12 Not applicable Not applicable Not applicable	RELATIVE DENSITY SOLUBILITY IN WATER @ 20°C PARTITION COEFFICIENT (n-octanol/water)	2.7 g/ml <15 g/100g Not available
EVAPORATION RATE FLAMMABILITY (SOLID/GAS) UPPER EXPLOSIVE LIMIT LOWER EXPLOSIVE LIMIT VAPOUR PRESSURE VAPOUR DENSITY (AIR=1)	Not applicable Not applicable Not Available Not Available Not applicable Not applicable	AUTO IGNITION TEMPERATURE DECOMPOSITION TEMPERATURE °C VISCOSITY mPa.s @ 25°C EXPLOSIVE PROPERTIES OXIDIZING PROPERTIES	Not available Not available Not applicable Not available Not oxidising

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 10.2 10.3	Reactivity Chemical Stability Possibility of Hazardous reactions	Stable under normal conditions. Stable under recommended storage and handling conditions. No dangerous reaction known under conditions of normal use				
10.4 10.5	Conditions to Avoid Incompatible materials	No decomposition if stored and applied as directed. Incompatible with strong acids, alkaline materials, iron containing materials. Aqueous solutions will react with aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon monoxide.				
10.6	Hazardous Decomposition Products	No hazardous decomposition products if stored and handled as prescribed/ indicated.				

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects of the mixture

Acute toxicity	Contains con routes: skin,	•	that are hazardous lation.	by the following
LD 50 ORAL TOXICITY IN RATS LD50 DERMAL TOXICITY RABBITS LC 50 INHL TOXICITY IN RATS LD50 DERMAL TOXICITY RABBITS LC 50 ORAL TOXICITY IN RATS LD50 DERMAL TOXICITY RATS	3400 >5000 >2.06	5. 5	Sodium silicate Sodium silicate Sodium silicate	

Skin corrosion/ irritation
Serious eye damage/ irritation
Respiratory or skin sensitisation
Germ cell mutagenicity
Carcinogenicity

Irritating
Damaging
Not classified
Not classified

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis cause by deposition in the lungs of fine respirable particles of crystalline silica.

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

Reproductive toxicityNot classifiedSpecific Target Organ Toxicity (Repeated Exposure)STOT RE2Specific Target Organ Toxicity (Single Exposure)Not classifiedAspiration hazardNot classified

11.2 Other information

In 1997, IARC (International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

LL 50 Fish EC 50 Invertebrates EL 50 Algae	(96 hr) (48 hr) (72hr)	sodium silicate 1108 1700 Not available	mg/l mg/l ma/l	Brachydanio rerio Daphnia magna Selenastrum capricornutum
LL 50 Fish	(96 hr)	Not available	mg/l	Lepomis macrochirus
EC 50 Invertebrates	(48 hr)		mg/l	Daphnia magna
EL 50 Algae	(72hr)		mg/l	Selenastrum capricornutum

Microorganisms/ effect upon activated sludge

EC₅₀ Bacteria (3.0 hr) mg/l Activated sludge, domestic

12.2 Persistence and Not biodegradable degradability

12.3 Bioaccumulative potential Not available

12.4 Mobility in soil Sinks in water. A proportion (<15%) is water soluble. If

the product enters soil, it will be mobile and may

contaminate groundwater.

12.5 Results of PBT and vPvB

assessment

PBT: This mixture contains no substances considered as

PBT

vPvB: This mixture contains no substances considered

as vPvB

12.6 Other adverse effects

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters. This product has not been tested. The statement has been derived from products of a similar structure and composition.

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SECTION 13: DISPOSAL CONSIDERATION

13.1 Waste treatment methods

Dispose of contents/ container according to the end user disposal procedure (P501). Dispose by landfill via a licensed waste disposal contractor in accordance with local and national regulations.

Contaminated packaging should be emptied as far as possible, they can then be recycled after being thoroughly cleaned by a licensed contractor. Labels must not be removed from containers until they have been cleaned. Packaging materials that are not contaminated should be treated as household waste or as recycling material.

13.2 Additional information

The UK Environmental Protection (Duty of Care) regulations (EP) and amendments should be noted (United Kingdom)

SECTION 14: TRANSPORT INFORMATION

14.1 UN number NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.2 Proper shipping name NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.3 Transport Hazard Class NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.4 Packing Group NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.5 Environmental hazards NOT CLASSIFIED

ADR

RID

IMDG

IATA

ADN

14.6 Special Precautions for user

Not classified as dangerous in the meaning of transport regulations

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code Not applicable

Print date 17/07/2023 7/8 SDS –Sauereisen P78-3 July 2023

Date Revised : 12/07/2023 Revision : 13

Product : **ELECTRIC RESISTOR CEMENT Nº78/3**

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the mixture

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793193 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Employment restrictions: Observe employment restrictions for young people, for child bearing mothers/ nursing and for women of child-bearing age.

15.2 Chemical Safety Assessment

Assessed to be not PBT/vPvB. No risk management measures as defined by REACH have been identified.

SECTION 16: OTHER INFORMATION *

SECTIONS REVISED 2 Supersedes date 18/02/2022

Removal of section 2.1.2

Legend

PBT Persistent, Bioaccumulative and Toxic VPVB very Persistent and very Bioaccumulative

Data sources Supplier information

Other hazard and risk phrases listed in this MSDS

H335 May cause respiratory irritation

Training advice General industrial hygiene practice. Do not eat, drink or smoke when

using this product (P270)

Manual handling

Further information

This information relates only to the specific material designated and is to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness and without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressively agreed in writing or construed as recommending the use of any product in conflict of any patent. All goods are supplied subject to Glassbond Ltd's General Conditions of Sale.